

Infrared-Thermometer with NiCr-Ni Connection

TFI 650



Technical Data

Type	TFI 650
Measurement range	-60 °C ... +1500 °C
Accuracy	±2% of measurement value / ±2 °C (whichever is larger)
Resolution	0.1 °C
Response time	Approximately 1 sec
Emissivity factor	0.1 ... 1.0
Distance:spot ratio	50:1
Probe	With SMP connection
Operating temperature	0 °C ... +50 °C
Storage temperature	-20 °C ... +65 °C
Housing material	ABS
Protection class	IP 20
Battery	2 x AAA (Micro)
Battery lifetime	Typically 140 hours
Dimensions	47 x 197 x 203.3 mm
Weight	Approximately 385 g (with battery)
Certificate	Factory calibration certificate

TFI 650



Applications

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> • Temp. measurements up to +1500 °C • Measuring and monitoring tasks in industry, trade and craft | <ul style="list-style-type: none"> • Air-conditioning systems • Laboratory | <ul style="list-style-type: none"> • Storage • Incoming goods |
|--|--|---|

Attributes

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> • Infrared for non contact temperature measurement • Distance : spot ratio = 50:1 | <ul style="list-style-type: none"> • Double laser pointer • Switchable between °C / °F • Alarm at MIN / MAX exceed | <ul style="list-style-type: none"> • NiCr-Ni connection • Factory calibration certificate |
|--|---|---|

Description	Type	Part No.
Infrared Thermometer with NiCr-Ni connection	TFI 650	1340-1783

Comments

Optional external NiCr-Ni probes with SMP connection available (pages 11- 19).